PREMIER





MT35P12

SUPERIOR SPRAY CAPABILITIES.









PREMIER - MT35P12

The Premier™ MT35P12 tackles tasks with confidence and precision because of the Versalift TC34 aerial lift, displaying a working height of 37 ft (11.2 m). Ensure consistent and reliable results in even the most challenging weather conditions with the recirculating heat system that helps heat fluid faster. Complimented with the Express Heat Single-Pass Instant Heating, the MT35P12 streamlines your workflow that keeps you ahead of schedule. Guardian Technology allows for concentrated movement and control that positively influences productivity. Take control with the Premier MT35P12 in-cab control panel, allowing you to oversee and operate all functions from the comfort of the cabin.

Cummins ISB Diesel EPA Tier / Certification Level Tier IV Engine Diesel Engine Type USLD Fuel 408 CID (6.7 L) Displacement 2,600 RPM Governed RPM with Full Load 260 @ 2,400 RPM Net HP at Governed RPM 660 lb-ft @ 1,600 RPM Torque 950 @ 1800 RPM AUXILLARY POWER Auxiliary Engine Perkins 404 Diesel			
Engine Diesel Engine Type USLD Fuel 408 CID (6.7 L) Displacement 2,600 RPM Governed RPM with Full Load 260 @ 2,400 RPM Net HP at Governed RPM 660 lb-ft @ 1,600 RPM Torque 950 @ 1800 RPM			
Type USLD Fuel 408 CID (6.7 L) Displacement 2,600 RPM Governed RPM with Full Load 260 @ 2,400 RPM Net HP at Governed RPM 660 lb-ft @ 1,600 RPM Torque 950 @ 1800 RPM			
Fuel 408 CID (6.7 L) Displacement 2,600 RPM Governed RPM with Full Load 260 @ 2,400 RPM Net HP at Governed RPM 660 lb-ft @ 1,600 RPM Torque 950 @ 1800 RPM			
Displacement 2,600 RPM Governed RPM with Full Load 260 @ 2,400 RPM Net HP at Governed RPM 660 lb-ft @ 1,600 RPM Torque 950 @ 1800 RPM AUXILLARY POWER			
Governed RPM with Full Load 260 @ 2,400 RPM Net HP at Governed RPM 660 lb-ft @ 1,600 RPM Torque 950 @ 1800 RPM AUXILLARY POWER			
Net HP at Governed RPM 660 lb-ft @ 1,600 RPM Torque 950 @ 1800 RPM AUXILLARY POWER			
Torque 950 @ 1800 RPM AUXILLARY POWER			
AUXILLARY POWER	М		
Auxiliary Engine Perkins 404 Diesel			
	Auxiliary Engine Perkins 404 Diesel		
Type Tier 4F 4 Cylinder Turl Diesel Engine	ocharged		
Fuel Diesel			
Displacement 134 CID (2.2 L)			
Governed RPM with Full Load 1,800 RPM			
Net Brake HP at Governed RPM 42 hp			
Torque 74 Nm @ 1,500 rpm			

DIMENSIONS	
Length - Open Basket	344" [8,737 mm]
Width	96" (2,439 mm)
Height	161" [4,089 mm]
Wheel Base	180.7" (4,589 mm)
Weight	22,120 lbs (10,033 kg)

PERFORMANCE	
Maximum Governed Speed (Boom Raised)	4 mph (6.4 km/h)
Overhead View Cap w/ Dual Pantograph Wiper	632 sq in Slanted Viewing Capacity
Communication System	David Clark® 3800 Series
Lift Working Height (Open Basket)	37' [11,278 mm]
Aerial Lift Basket Capacity	300 lbs (136 kg)
Aerial Lift Rotation	370 Degrees Non Continuous
Deice Pump (Centrifugal)	55 gpm (210 lpm) @ 150 psi
Anti-Ice Pump (Diaphram)	22.5 gpm (85 lpm) @ 50 psi
Deice Fluid Tank	900 gal (3,407 L) Stainless Steel
Anti-Ice Fluid Tank	300 gal (1,136 L) Stainless Steel
Generator	20 kW 240 Volt 3 Ph

