





## TMD-180/250/270

STREAMLINE OPERATIONS.









## TUG - TMD-180/250/270



| CHASSIS POWER                               |                                       |  |
|---|---------------------------------------|--|
| TMD180 - Cummins QSX15 435 HP               |                                       |  |
| Fuel & Compatible Fuel<br>(Type & Quantity) | ULSD Only 110 US gal<br>[416 L] (all) |  |
| Displacement (Size of Engine)               | 14.9 L                                |  |
| Governed RPM with Full Load                 | 1,900                                 |  |
| Net Brake HP at Governed RPM                | 435 [324 kW]                          |  |
| TMD250 - Cummins QSX15 535 HP               |                                       |  |
| Fuel & Compatible Fuel<br>(Type & Quantity) | ULSD Only 110 US gal<br>(416 L) (all) |  |
| Displacement (Size of Engine)               | 14.9 L                                |  |
| Governed RPM with Full Load                 | 1,900                                 |  |
| Net Brake HP at Governed RPM                | 535 (399 kW)                          |  |
| TMD270 - Cummins QSX15 600 HP               |                                       |  |
| Fuel & Compatible Fuel<br>(Type & Quantity) | ULSD Only 110 US gal<br>(416 L) (all) |  |
| Displacement (Size of Engine)               | 14.9 L                                |  |
| Governed RPM with Full Load                 | 1,900                                 |  |
| Net Brake HP at Governed RPM                | 600 (447 kW)                          |  |

| DIMENSIONS                    |                      |  |
|-------------------------------|----------------------|--|
| TMD18D - Cummins QSX15 435 HP |                      |  |
| Width                         | 82" (2,083 mm)       |  |
| Wheelbase                     | 148" (3,759.2 mm)    |  |
| Height                        | 92.5" (2,350 mm)     |  |
| Standard Weight               | 11,050 lb (5,023 kg) |  |
| Length (without Hitches)      | 176" (4,471 mm)      |  |
| Ground Clearance              | 8.5" (215.9 mm)      |  |
| TMD250 - Cummins QSX15 535 HP |                      |  |
| Width                         | 82" (2,083 mm)       |  |
| Wheelbase                     | 148" (3,759.2 mm)    |  |
| Height                        | 92.5" (2,350 mm)     |  |
| Standard Weight               | 12,300 lb (5,580 kg) |  |
| Length (without Hitches)      | 176" (4,471 mm)      |  |
| Ground Clearance              | 8.5" (215.9 mm)      |  |
| TMD270 - Cummins QSX15 600 HP |                      |  |
| Width                         | 82" (2,083 mm)       |  |
| Wheelbase                     | 148" (3,759.2 mm)    |  |
| Height                        | 92.5" (2,350 mm)     |  |
| Standard Weight               | 13,300 lb (6,033 kg) |  |
| Length (without Hitches)      | 176" [4,471 mm]      |  |
| Ground Clearance              | 8.5" (215.9 mm)      |  |
|                               |                      |  |

| PERFORMANCE                    |  |
|--------------------------------|--|
| TMD180 - Cummins QSX15         | 435 HP   |
| Mass Flow Output               | 180 lb (82 kg) / min at 68F (20c)                              |
| EPA Tier / Certification Level | Tier 4F  |
| Туре                           | Water-Cooled, Direct Injected, 6<br>Cylinder, Turbocharged CAC |
| Speed (Idle)                   | 1000 RPM   |
| Speed (Max. When Loaded)       | 2100 RPM   |
| Max Tow Speed                  | 15 mph (24.1 km/h)   |
| TMD250 - Cummins QSX15         | i 535 HP   |
| Mass Flow Output               | 250 lb (113.4 kg)/min at 68F<br>(20C) 1,800 RPM                |
| EPA Tier / Certification Level | Tier 4F  |
| Туре                           | Water-Cooled, Direct Injected, 4<br>Cylinder, Turbocharged     |
| Speed (Idle)                   | 1000 RPM   |
| Speed (Max. When Loaded)       | 2200 RPM   |
| Max Tow Speed                  | 15 mph (24.1 km/h)   |
| TMD270 - Cummins QSX15         | i 600 HP   |
| Mass Flow Output               | 270 lb (122.5 kg)/min at 68F<br>(20C) 2,000 RPM                |
| EPA Tier / Certification Level | Tier 4F  |
| Туре                           | Water-Cooled, Direct Injected, 6<br>Cylinder, Turbocharged CAC |
| Speed (Idle)                   | 1000 RPM   |
| Speed (Max. When Loaded)       | 2200 RPM   |
| Max Tow Speed                  | 15 mph (24.1 km/h)   |